



OP-8 WD

Conveyor Chain & Trolley Wheel Cleaner

OPCO® Model OP-8 WD

Designed for applications where moisture and humidity is prevalent, due to sanitary wash-downs or exposure to manufacturing processes, the OP-8 Wash-Down Duty Conveyor Chain & Trolley Wheel Cleaner reduces downtime while it cleans your conveyor system. Cleans chain, trolley wheels and trolley brackets. Fits all sizes of overhead monorail or power & free conveyors, and drop finger slider conveyors.



FEATURES/BENEFITS

- Automatically cleans while conveyor is in operation
- Eliminates expensive, time-consuming manual cleaning
- Removes process build-up, dirt, rust, scale, and/or paint
- Stainless steel hardware provides long life in moist conditions
- 2HP 230/460vac TEFC 3-phase motor p efficient operation
- Wash-down duty brush shaft bearings and wash-down duty electric motor for long life in moist conditions
- Brushes shaped for your conveyor, for efficient operation
- Split brush shafts for easy, one-bolt removal of each brush assembly. Replacement brushes can be purchased assembled for one-bolt installation of each side.
- Brush tension can be adjusted while conveyor is in operation
- Reduces drag on drive motors, extending life
- Compact, rugged cleaner is easy to install and
- Overhead, drop finger, inverted and floor conveyors

OPTIONAL EQUIPMENT

- Electric timer for automatically starting and stopping cleaner action at any desired intervals
- Other voltages available
- Brush-fill materials include: crimped steel wire, Tampico, and White Polypropylene which are commonly used in food processing plants
- Longer brush shafts for cleaning conveyor attachments
- Totally enclosed metal shroud



Split Shaft allows one-bolt removal of brush assembly

TECHNICAL ASSISTANCE

Customized Technical Assistance Programs are available.

WARRANTY

A limited warranty is provided with each OP-8WD.

SPECIFICATIONS	
Motor	2 hp, 208-220/440-480 V, 60 cycle, 3 phase
Bearings	Heavy duty, sealed, wash-down duty, self-aligning
Housing	Thick-walled cast aluminum for greater strength
Shafting	1in diameter stainless steel handles max loads
Brushes	Brush material based on customer application
Guards	Neoprene rubber curtains surround brushes
Dimensions	24in W x 24in D x 32.5in H